



Pos.	A	B
8	13.1	6.0
10	15.1	8.0
12	17.1	10.0
14	19.1	12.0
16	21.1	14.0
20	25.1	18.0
22	27.1	20.0
26	31.1	24.0
30	35.1	28.0
34	39.1	32.0
40	45.1	38.0
44	49.1	42.0
50	55.1	48.0
68	73.1	66.0

**SPECIFICATIONS**

- Current rating: 1 amp
- Contact material: Phosphor bronze
- Contact resistance: 30 milliohms max.
- Insulator material: PBT, glass reinforced, UL94V-0, black
- Insulation resistance: 3,000 megohms min.
- Withstanding: 500VAC for 1 min.
- Wire: 1.00mm pitch flat ribbon cable
- Operating temperature: -40°C to +105°C

Series	Type	Positions	Polarization	Plating
BFC	B	XX	XX	XX
2mm flat cable socket	B=Multi contact	08-68 (see chart)	P=Polarized NP=No polarization	TN=Tin SGXX=Selective gold GDXX=Gold XX=Flash if blank; 05, 10, 15, 30µ" gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BFC-B-XX-XX-XX**

Description: IDC socket, multi-contact type