



SPECIFICATIONS

- Operating voltage: 250VAC max.
- Current rating: 3 amps max.
- Contact material: Phosphor bronze
- Contact plating: Gold over nickel
- Contact resistance: 20 milliohms max.
- Insulator material: PBT, glass reinforced, UL94V-0
- Insulation resistance: 5,000 megohms min.
- Withstanding: 1,000 VAC for 1 min.
- Operating temperature: -55°C to +105°C

E196498

Series	Positions	Polarization	Finish	Options
AFC	XX	XX	XX	XXX
Flat cable socket	6 to 64	P=Polarized NP=Not polarized	SGXX=Selective Gold XX=flash if blank 15,30 u"	[blank]=None ASR=Strain relief APT=Pull tab AKY=Keying plug DW=Dual wipe

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **AFC-XX-XX-XX-XXX**

Description: Flat cable socket, .100" by .100"