



SPECIFICATIONS

Current rating:	1 amp
Contact material:	Phosphor bronze
Contact plating:	Tin, selective gold, gold flash, gold plate
Insulator material:	PBT, glass reinforced, UL94V-0
Withstanding:	500VAC for 1 min.
Contact resistance:	30 milliohms max.
Insulation resistance:	3,000 megohms min.
Operating temperature:	-40°C to +105°C
Terminates with:	2.54mm pitch flat ribbon cable

Available Only On
Central Components
Cables

Series	No. of Contacts	Contact Plating
AFCA-SL	XX	XX
IDC socket single row, slim type	2-36	TN=Tin plate GDXX=Gold flash SG=Selective gold XX=5μ", 10μ", 15μ", 30μ" gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
A	P/N table fixed	10/15/07		Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35 0.00 ± 0.20 Angles ± 3'		
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **AFCA-SL-XX-XX**

Description: IDC socket single row, 2.54mm pitch, slim type