



TABLE A

LOCK	DESCRIPTION
LOCK	
LOCK	
	DESCRIPTION

Dimensions		
Code	A	L
A	Ø5.3	11.5
B	Ø5.8	11.1
C	Ø6.2	10.9
D	Ø6.5	11.3
E	Ø7.0	10.8

SPECIFICATIONS
 Rating: 100V AC Max or 12V DC 2A Max
 Insulation Resistance: 50MΩ Min at 250V DC
 Withstanding: 250V AC at 1 minute
 Plastic Cover: ABS
 Shell: Brass, Nickel Plating
 POM Ring: POM
 Housing: PBT
 Pin: Brass, Gold Flash
 Spring: Steel, Nickel Plating
 Metal Cap: Brass, Tin Plating
 Strength: 2.5kgf Min

RoHS compliant

Series	Positions	Wire Inlet	Options
CMDX	XX	X	X
Wire Mount Mini DIN X: P=Male S=Female	03-08	See Table	Blank=None L=Lock

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/15/09
				Checked	Lizzy	05/15/09
				Drawn	Tina	05/15/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMDX-XX-X-L**

Description: Wiremount Mini DIN