



SPECIFICATIONS

Current rating:	5 amps
Contact material:	Brass
Contact plating:	Gold flash
Contact resistance:	15 milliohms max.
Insulation material:	PBT+30% glass fiber, UL94V-0
Insulation resistance:	1,000 megohms min.
Withstanding:	500VAC for 1 min.
Clinched nut material:	Brass
Clinched nut plating:	Nickel
Shell material:	Steel
Shell plating:	Tin or yellow chromate
Temperature range:	-50°C to +100°C

Dimensions (mm)			
Pos.	A	B	C
9	30.80	24.99	16.30
15	39.15	33.32	24.65
25	53.00	47.04	38.40
37	69.30	63.50	54.80
50	67.00	61.00	52.20

Series	Type	Tail options	Face options	Other options
DSXX	XX	X	XXX	XX
D-sub connector XX=Pins 9, 15, 25, 37, 50	FT=Female vertical mount MT=Male vertical mount MHT=Male high profile FHT=Female high profile	A=Standard for .052" to .125" PCB B=Wire wrap	[blank]=.120" thru hole RCN=Clinch nut RJS=Jackscrew RSB=Standoff with board locks	[blank]=None FF=Ferrite filter YC=Yellow chromate shell

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **DSXX-MT-A-RCN-XX**

Description: D-subminiature connector, male, straight PCB tail, standard profile