



SPECIFICATIONS

- Insulator: PBT Glass Reinforced, UL94V-0
- Contact: Phosphor Bronze or Brass
- Current Rating: 1 Amp
- Contact Resistance: 30m ohms max.
- Insulation Resistance: 3000 M ohms min.
- Withstanding: 500V AC for 1 minute
- Operating Temp: -40°C ~ +105°C
- Flat Ribbon Cable with 1.27mm Pitch

Dimensions			
Pos.	A	B	C
10	22.36	10.16	13.04
14	27.44	15.24	18.12
16	29.98	17.78	20.66
20	35.06	22.86	25.74
26	42.68	30.48	33.36
34	52.84	40.64	43.52
40	60.46	48.26	51.14
50	73.16	60.96	63.84

Series	Contacts	Finish	Color	Options
FCCE	XX	GDXX	XX	XXX
Flat cable card edge connector	w/o Mounting Ears 10,14,16,20,26,34,40,50 With Mounting Ears 10,20,26,34,40,50	GDXX=Gold XX=Flash if Blank, 3,5,10,15,30 u"	BK=Black GY=Gray	Blank=No Mounting Ears MER-A=Type A Mounting Ears MER-B=Type B Mounting Ears KY=Key

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **FCCE-XX-GDXX-XX**

Description: Card Edge Connector