



SPECIFICATIONS

Current rating:	1 amp
Contact material:	Phosphor bronze
Contact plating:	Tin, selective gold, gold flash, gold plate
Insulator material:	PBT, glass reinforced, UL94V-0
Withstanding:	500VAC for 1 min.
Contact resistance:	30 milliohms max.
Insulation resistance:	3,000 megohms min.
Operating temperature:	-40°C to +105°C
Terminates with:	1.0mm pitch flat ribbon cable

Series	Contacts	Contact Plating
FCPA-C	XX	XX
2.0mm pitch transition plug	8, 10, 12, 14, 16, 20, 22, 24, 26, 30, 34, 40, 44, 50, 68	TN=Tin plate; SG=Selective gold; GD=Gold flash; GD05=5µ" gold; GD10=10µ" gold; GD15=15µ" gold; GD30=30µ" gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **FCPA-C-XX-XX**

Description: Transition plug, 2.0mm pitch