


SPECIFICATIONS

Current rating: 1 amp
 Contact material: Phosphor bronze
 Contact plating: Tin, selective gold, gold flash, gold plate
 Insulator material: PBT, glass reinforced, UL94V-0
 Withstanding: 500VAC for 1 min.
 Contact resistance: 30 milliohms max.
 Insulation resistance: 3,000 megohms min.
 Operating temperature: -40°C to +105°C
 Terminates with: 1.27mm pitch flat ribbon cable

POSITION	A	B
14	19.40	15.24
16	21.94	17.78



Recommended PC Board Layout

Series	Contacts	Contact Plating
FDPA-LP	XX	XX
2.54mm pitch DIP plug, low profile	14, 16 contacts	TN=Tin plate, SG=Selective gold, GD=Gold flash, GD05=5μ" gold, GD10=10μ" gold, GD15=15μ" gold, GD30=30μ" gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	8/10/99
				Checked	Lizzy	8/10/99
				Drawn	Tina	8/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **FDPA-LP-XX-XX**

Description: .254mm pitch DIP plug, low profile