



Dimensions		
Poles	A	B
2	.098	.256
3	.197	.354
4	.295	.453
5	.394	.551
6	.492	.650
7	.591	.748
8	.689	.846
9	.787	.945
10	.886	1.043
11	.984	1.142
12	1.083	1.240
13	1.181	1.339
14	1.280	1.437
15	1.378	1.535
16	1.476	1.634

SPECIFICATIONS
 Current Rating: 3A AC, DC
 Voltage Rating: 250V AC, DC
 Poles: 2-20
 Material: Nylon 66 UL94V-0
 Insulation Resistance: 1000MΩ min.
 Applicable Wire: AWG #28-22
 PCB Thickness: .047", .063"
 Color: White, White-Ivory
 Withstanding: 800V AC
 Temperature Range: -25C to +85C

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	02/09/07
				Checked	Lizzy	02/09/07
				Drawn	Tina	02/09/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-1137B-XX**

Description: 0.98" Pitch Board-in Connector Housing

