



SPECIFICATIONS

Voltage rating: 250V AC/DC
 Current rating: 3A AC/DC
 Contact resistance: 20 milliohm max.
 Material: Nylon 66 UL 94V-0
 Insulation resistance: 1000megohm min.
 Withstanding: 800V AC/1-min
 Operating temp.: 25°C to 85°C
 Packaging: 1000 pc bag

Poles	A	B
2	2.50	6.50
3	5.00	9.00
4	7.50	11.50
5	10.00	14.00
6	12.50	16.50
7	15.00	19.00
8	17.50	21.50
9	20.00	24.00
10	22.50	26.50
11	25.00	29.00
12	37.50	31.50
13	30.00	34.00
14	32.50	36.50
15	35.002	39.00
16	37.50	41.50

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	8/10/99
				Checked	Lizzy	8/10/99
				Drawn	Tina	8/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-1137R-XX**

Description: 2.5mm cCrimp housing