



SPECIFICATIONS

Current rating: 1 amp
 Contact material: Brass
 Contact plating: Tin, selective gold, gold flash, gold
 Insulator material: PBT, glass reinforced, UL94V-0
 Withstanding: 250VAC for 1 min.
 Contact resistance: 30 milliohms max.
 Insulation resistance: 3,000 megohms min.
 Withstanding: 500VAC for 1 min.
 Operating temperature: -40°C to +105°C
 Terminates with: 1.27mm pitch flat ribbon cable

Accessories	X	Y
Long Latch	29.2	14.6
Short Latch	25.6	10.6

Dimensions						
Pos.	A	B	C	D	E	F
10	32.12	27.94	10.16	21.60	18.12	47.42
14	37.20	33.02	15.24	26.68	23.20	52.50
16	39.74	35.56	17.78	29.22	25.74	55.04
20	44.82	40.64	22.86	34.30	30.82	60.12
24	49.90	45.72	27.94	39.38	35.90	65.20
26	52.44	48.26	30.48	41.92	38.44	67.74
30	57.52	53.34	35.56	47.00	43.52	72.82
34	62.60	58.42	40.64	52.08	48.60	77.90
40	70.22	66.04	48.26	59.70	56.22	85.52
50	82.92	78.74	60.96	72.40	68.92	98.22
60	95.62	91.44	73.66	85.10	81.62	110.92
64	100.70	96.52	78.74	90.18	86.70	116.00

Series	Contacts	Contact Plating	Latch Length	Accessories
SLH	XX	XX	XX	XXX
.100"x.100" shrouded IDC latch header	10, 14, 16, 20, 24, 26, 30, 34, 40, 50, 60, 64	TN=Tin plate, SG=Selective gold, GD=Gold flash, GD05=5µ" gold, GD10=10µ" gold, GD15=15µ" gold, GD30=30µ" gold	SL=Short latch LL=Long latch	[blank]=Without mounting ears MER=With mounting ears

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **SLH-XX-XX-XX-XXX**

Description: Shrouded IDC latch header, .100"x.100" pitch