



POSITION	A	B	C
6P	11.14	4.00	2.0
8P	13.14	6.00	2.0
10P	15.14	8.00	2.0
12P	17.14	10.00	2.0
14P	19.14	12.00	2.0
16P	21.14	14.00	2.0
18P	23.14	16.00	2.0
20P	25.14	18.00	2.0
22P	27.14	20.00	2.0
24P	29.14	22.00	2.0
26P	31.14	24.00	2.0
28P	33.14	26.00	2.0
30P	35.14	28.00	2.0
34P	39.14	32.00	2.0
36P	41.14	34.00	2.0
38P	43.14	36.00	2.0
40P	45.14	38.00	2.0
44P	49.14	42.00	2.0
48P	53.14	46.00	2.0
50P	55.14	48.00	2.0
60P	65.14	58.00	2.0
64P	69.14	62.00	2.0

SPECIFICATIONS
 Operating voltage: 250VAC max.
 Current rating: 1 amps max.
 Contact material: Phosphor bronze
 Contact plating: Gold over nickel
 Contact resistance: 30 milliohms max.
 Insulator material: PBT, glass reinforced, UL94V-0
 Insulation resistance: 5,000 megohms min.

Series	Positions	Polarized	Plating	Option
AFCC	XX	X	XX	XX
IDC socket	See chart	P=Polarized NP=No Polarization	GDXX=Gold XX=Flash if blank, 03,05,10,15,30μ"	Blank=None GY=Gray SR=Strain relief

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/30/10
				Checked	Lizzy	08/30/10
				Drawn	Tina	08/30/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **AFCC-XX-X-XX-XX**

Description: Flat cable socket

