



Recommended P.C.Board  
Hole Layout

**SPECIFICATIONS**

Current Rating: 3 Amp  
 Contact Material: Copper Alloy  
 Contact Resistance: 20mΩ Max  
 Insulation Material: Polyester, UL94V-0  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding: 600V AC  
 Operating Temp: -40°C to +105°C

Series	Rows	Position	Type	CSL (A/B)	Plating
APH	2	XX	G212	Pin Lengths	XX
Pin Header .100x.100	2=dual row	04-80	R/A, 7.4x6.4 Profile	See Chart	TN=Tin SG=Selective Gold GD=Gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/31/05
				Checked	Lizzy	10/31/05
				Drawn	Tina	10/31/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **APH-2-XX-G212-CSL(.315/.110)-XX**

Description: 2.54 Pin Header Dual Row R/A Type Base 6.40H