



SPECIFICATIONS
 Current Rating: 3A
 Insulator Material: Thermoplastic UL94V-0
 Contact Material: Copper
 Insulation Resistance: 1000MΩ min.
 Contact Resistance: 20mΩ maximum
 Withstanding: AC 500V
 Temperature Range: -40C to +105C

Series	Rows	Style/Profile	Positions	Plating
ARS	01	BELPX	XX	XX
.100 pitch receptacle strip	01=Single	BELP=Bottom Entry 5mm Profile, 5.08mm tail spacing For single row BE even pins add 1 for 1st first, 2 for 1st first	04-80	TN=Tin SGXX=Selective Gold GDXX=Gold XX=Flash if blank, 3,5,10,15u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/15/11
				Checked	Lizzy	05/15/11
				Drawn	Tina	05/15/11
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **ARS-01-BELP-XX-XX**

Description: straight single row bottom entry receptacle strip