



**Recommended
P.C. Board Hole Layout**

SPECIFICATIONS

Current Rating: 3 Amps
 Contact Material: Brass
 Contact Plating: Gold Flash (standard)
 Contact Resistance: 20m ohms max.
 Insulation Material: Polyester, UL94V-0 P.B.T.
 Withstanding: AC 600V
 Operating Temp: -40°C ~ +105°C

RoHS compliant

Series	Rows	Type	Contacts	Plating	Options
ARS	XX	XX	XX	XX	XX
Receptacle strip	01=Single row 02=Dual row 03=Single row right angle 04=Dual row right angle	[blank]=Top Entry DE=Dual entry BE=Bottom entry SE=Side entry	Single row: 3-36 Dual row: 6-72	TN=Tin GDXX=Gold, SGXX=Selective Gold XX=Flash if blank 10,15,30u"	[blank]=None SM=Surface mount RT=Retention tails P=Polarized HT=High Temp

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	5/28/08
				Checked	Lizzy	5/28/08
				Drawn	Tina	5/28/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **ARS-02-XX-XX**

Description: Female Header P2.54 X 2.54mm, Dual Row Straight