



Current rating: 3 amps
 Contact Material: Brass
 Insulator Material: Polyester, UL94V-0 PBT
 Contact Resistance: 20m ohms max.
 Insulator Resistance: 1000 Megohms min.
 Withstanding: AC 600V
 Operating Temp: -40°C ~ +105°C

Series	Rows	Options	Contacts	Plating	Special Options
ARS	XX	XX	XX	XX	XX
Receptacle strip	01=Single row 02=Dual row 03=Single row R/A 04=Dual row R/A	[blank]=None DE=Dual entry BE=Bottom entry SE=Side entry P=Polarized	Single row: 3-40 Dual row: 6-72	TN=Tin SGXX=Selective gold GDXX=Gold XX=Flash if blank; 15, 30, 50μ"	[blank]=None SM=Surface mount RT=Retention tails P4C=End Position Removed

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/05
				Checked	Lizzy	08/10/05
				Drawn	Tina	08/10/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **ARS-04-P-XX-XX-P4C**

Description: Female Header, 8.5mm, Dual Row, R/A