



SPECIFICATIONS
 Current Rating: 3 Amps
 Contact Material: Brass
 Contact Resistance: 20m ohms max.
 Insulator Material: Polyester, UL94V-0
 Insulation Resistance: 1000 Megohms min.
 Withstanding: AC 500V
 Operating Temp: -40°C ~ +105°C

Series	Type	Positions	Plating
ARS	XX	XX	XX
Receptacle Strip .100" X .100"	01=Single Row Straight 02=Double Row Straight 03=Single Row R/A 04=Double Row R/A	Single Row 1-40 Double Row 2-80	TN=Tin SGXX=Selective Gold GDXX=Gold XX=Flash if blank 15,30,50u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	09/26/08
				Checked	Lizzy	09/26/08
				Drawn	Tina	09/26/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **ARS-04-XX-XX**

Description: Receptacle Strip, double row, right angle