



SPECIFICATIONS

Current Rating: 3 Amps
 Contact Resistance: 20mΩ Max
 Withstanding: 1000V AC/DC
 Insulation Resistance: 1000MΩ Min
 Contact Material: Brass
 Contact Plating: Gold over Nickel
 Latch Material: Zinc, Nickel Plating
 Insulation Material: PBT or PA9T+30% GF UL94V-0
 Operating Temp: -40C to +105C

Accessories	D
Long Latch	14.55
Short Latch	10.65

Series	Contacts	Mounting Type	Plating Options	Options
BHD	XX	XX	XX	XXX
Box header .100" x .100"	6,8,10,12,14,16,20 ,24,26,30,34,40,50 ,60,64	ST=Straight RA=Right Angle RASM=Right angle surface mount	SGXX=Selective gold (only) XX=Flash if blank; 05,10,30,50u"	[blank]=None SPL=Special pin length LLC=Long side latch SLC=Short side latch

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BHD-XX-ST-SG-XLC**

Description: Shrouded header with side latches