


| Dimensions | | | |
|------------|-------|-------|-------|
| Pos. | A | B | C |
| 10 | 26.52 | 17.96 | 10.16 |
| 14 | 31.60 | 23.04 | 15.24 |
| 16 | 34.14 | 25.58 | 17.78 |
| 20 | 49.22 | 30.68 | 22.86 |
| 24 | 44.30 | 25.74 | 27.94 |
| 26 | 46.84 | 38.28 | 30.48 |
| 30 | 51.92 | 43.36 | 35.56 |
| 34 | 57.0 | 48.44 | 40.64 |
| 40 | 64.62 | 56.06 | 48.26 |
| 50 | 77.32 | 68.76 | 60.96 |
| 60 | 103.7 | 94.16 | 73.66 |
| 64 | 107.8 | 99.24 | 78.74 |

SPECIFICATIONS

Contact material: Brass
 Contact plating: Gold flash over nickel
 Insulator material: PBT



Recommended PC Board Layout

| Series | Positions | Mounting | Plating | Latches | Options |
|------------|-----------|-------------------------------|--|---|--|
| BHD | XX | XX | XX | XX | XX |
| Box header | See chart | ST=Straight RA=Right angle | GD=Gold SG=Selective gold TN=Tin | SL=Short latch (3.9mm) LL=Long latch (7.68mm) NL=No latch | [blank]=None SM=Surface mount SPL=Special pin length |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 08/10/99 |
| | | | | Checked | Lizzy | 08/10/99 |
| | | | | Drawn | Tina | 08/10/99 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3° |
| | | | | UNIT: mm | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BHD-XX-RA-GD-SL**
 Description: Box header, right angle, with end latches, PCB thru hole mount