



P.C.Board Layout



**SPECIFICATIONS**

Contact Material:	Brass
Contact Plating:	Gold Over Nickel
Insulator Material:	Nylon 6T, Black
Solder Plating:	Tin Over Nickel
Operating Temp:	260°C 10sec

Series	Positions	Mounting	Plating	Latches	Options
BHD	XX	XX	XX	XX	XX
Box header	6-64	ST=Straight RA=Right angle	TN=Tin GDXX=Gold SGXX=Selective gold XX=[Flash if Blank]15µ", 30µ", 50µ" gold	[blank]=None SL=Short latch (3.9mm) LL=Long latch (7.68mm) NL=Empty latch holder	[blank]=None PF=Press Fit SM=Surface mount SPL=Special pin length HT=High Temperature

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/16/08
				Checked	Lizzy	12/16/08
				Drawn	Tina	12/16/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BHD-XX-ST-XX-HT**

Description: 2.54 Pitch Box Header Straight, High Temperature