



**SPECIFICATIONS**  
 Contact Resistance: 20mΩ max.  
 Withstanding: 500V AC / minute  
 Insulation Resistance: 1000MΩ Min.  
 Contact Retention Force: 1000gf Min.  
 Storage Temperature: -20°C ~ +70°C  
 Operating Temperature: 0°C ~ +85°C

TABLE A

TYPE	DIM.	E
TYPE 1		3.10
TYPE 2		8.00

Position	A	B	C
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.86
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.78	48.58	40.64
40	58.40	56.20	48.26
50	71.10	68.90	60.96
60	83.80	81.60	73.66
64	88.88	86.68	78.74

Series	Contacts	Mounting	Plating
BHD	XX	XX	GD
Box Header	10,12,14,16,20,26,30,34,40,50,60,64	ST=Straight RA=Right Angle	GD=Gold Flash

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/04/07
				Checked	Lizzy	07/04/07
				Drawn	Tina	07/04/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BHD-XX-XX-XX**

Description: Box Header 2.54 pitch