



SPECIFICATIONS

Current rating: 3 amps
 Operating voltage: 250 VAC
 Contact material: Phosphor bronze
 Contact plating: Tin, gold or duplex
 Contact resistance: 10 milliohms max.
 Insulator material: Nylon 6T, glass reinforced, UL94V-0
 Insulator resistance: 1,000 megohms min
 Withstanding: 1,000VAC for 1 min.
 Operating temperature: -55°C to +125°C
 Processing temperature: 230°C/60 sec.

RoHS compliant

Series	Insulator	Rows	Type	Positions	Contact Length	Plating	Options
BPH	X	X	XX	XX	XX	XX	XX
2mm Unshrouded Pin Headed	Blank=.079 (2.0mm) C=.059 (1.5mm)	1,2	Blank=Straight RA=Right Angle RRA=Reverse Right Angle SM=Surface Mount RASM=R/A Surface Mount	Single Row: 1-40 Double Row: 2-80	SD=.157 (4mm) Mating CSL=(A) or (A/E)	GD=Gold SG=Selective Gold TN=Tin	Blank=None CP=Centering Peg PPL=Pick & Place Pad TR=Tape & Reel TB=-Tube

Rev.	Description	Date	Approved	Drawing	Name	Date
A	RoHS	09/23/05	Tom	Approved	Howard	08/10/99
B	Spec	10/04/05	Tom	Checked	Lizzy	08/10/99
C	DWG	07/25/12	Greg	Drawn	Tina	08/10/99
D	PNT	8/02/12	Greg	0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BPH-2-RASM-XX-XX-XX**

Description: Pin header, 2mm pitch, right angle, surface mount

