



PANEL OPENING [ Recommended panel thickness:.062"(1.57mm) ]

**SPECIFICATIONS**

Current Rating: #20:5A, #22:5A, #24:4A, #26:3A, #28:2A, #30:1A  
 Voltage Rating: 250V AC, DC  
 Housing Material: Nylon 66, UL94V-0  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding: 1500V AC  
 Temperature Rise: 30°C Max.

Series	Style	Positions	Options
JS-A	3020	XXS	X
Crimp Terminal .118" Pitch	Style=3020	XX=see chart S=Single Row	Blank=none E=w/ Mounting Ears

Dimensions							
Circuits	A	B	C	Circuits	A	B	C
2	3.0±0.08	6.85	7.21	8	21.0±0.15	24.85	28.9
3	6.0±0.10	9.85	10.21	9	24.0±0.15	27.85	28.21
4	9.0±0.10	12.85	13.21	10	27.0±0.20	30.85	24.9
5	12.0±0.10	15.85	16.21	11	30.0±0.20	33.85	37.9
6	15.0±0.15	18.85	19.21	12	33.0±0.20	37.21	40.9
7	18.0±0.15	21.85	22.21				

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	3/21/03
				Checked	Lizzy	3/21/03
				Drawn	Tina	3/21/03
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-A-3020-XXS**

Description: .118 Single Row Plug Housing