



SPECIFICATIONS

Voltage rating: 250VAC
 Current rating: See chart
 Contact resistance: 10 milliohms max.
 Body material: Nylon, black, UL94V-0
 Insulation resistance: 100 megohms min.
 Withstanding: 1,500 VAC for 1min.
 Temperature rise: 30°C max.

Current rating	
AWG	Amps
20	5
22	5
24	4
26	3
28	2
30	1

Dimensions				
AWG	A	B	C	D
26-30	1.8	1.6	2.4	1.9
20-24	2.1	2.1	2.7	2.5

Series	Style	Size	Plating
JS-A	3030T	X	XX
Crimp terminal, .118" pitch	Style 3030T	1=26-30 AWG 2=20-24 AWG	TN=Tin SG=Selective gold GD=Gold flash

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
A	Desc.	2/26/09	Greg	Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-A-3030T-X-XX**

Description: Crimp terminal 10K Reel