



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 2A AC/DC
 Material: Brass, Tin Plated
 Contact Resistance: 20mΩ max
 Thickness: 0.2mm
 Insulation Resistance: 1000MΩ min
 Withstanding: 800V AC/minute
 Temperature Range: -25°C to +85°C

Dimensions	
Item	mm
T	0.2 ± 0.03
L	5.2 ± 0.25
IS	2.2 ± 0.25
WS	1.6 ± 0.25
H	1.9 ± 0.25
H1	1.4 ± 0.25
W	1.6 ± 0.1
W2	0.9 ± 0.05
E	5.5 ± 0.35
e	1.2 ± 0.25
t	0.5 ± 0.15

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/15/08
				Checked	Lizzy	12/15/08
				Drawn	Tina	12/15/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		


Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-1130R-T**

Description: 2.00mm Crimp Style Connectors Terminal