



**SPECIFICATIONS**

Voltage Rating: 250V AC/DC  
 Current Rating: 2A AC/DC  
 Material: Nylon 66 UL94V-0  
 Contact Resistance: 20mΩ max  
 Insulation Resistance: 1000MΩ min  
 Withstanding: 800V AC/minute  
 Temperature Range: -25°C to +85°C

Dimensions		
Poles	A	B
2	2.00	5.20
3	4.00	7.20
4	6.00	9.20
5	8.00	11.20
6	10.00	13.20
7	12.00	15.20
8	14.00	17.20
9	16.00	19.20
10	18.00	21.20
11	20.00	23.20
12	22.00	25.20
13	24.00	27.20
14	26.00	29.20
15	28.00	31.20
16	30.00	33.20
17	32.00	35.20
18	34.00	37.20
19	36.00	39.20
20	38.00	41.20

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/08/08
				Checked	Lizzy	10/08/08
				Drawn	Tina	10/08/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		


**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-1130R-XX**

Description: 2.00mm , Board In Top Entry Crimp Style Connector Housing