



SPECIFICATIONS

Voltage rating: 250V AC/DC
 Current rating: 3A AC/DC
 Insulation resistance: 1000M Ohms min.
 Contact resistance: 20m ohms max.
 Withstanding: 800 V AC/min
 Temp. range: -25°C to +85°C

Material: Nylon 66 UL 94V-0

Poles	Dimensions (mm)	
	A	B
2	2.50	7.00
3	5.00	9.50
4	7.50	12.00
5	10.00	14.50
6	12.50	17.00
7	15.00	19.50
8	17.50	22.00
9	20.00	24.50
10	22.50	27.00
11	25.00	29.50
12	27.50	32.00
13	30.00	34.50
14	32.50	37.00
15	35.00	39.50

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	11/11/08
				Checked	Lizzy	11/11/08
				Drawn	Tina	11/11/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-1131-XX**

Description: 2.5mm crimp connector wafer