



**SPECIFICATIONS**

Voltage Rating: 250V AC/DC  
 Current Rating: 3A AC/DC  
 Insulation Resistance: 1000MΩ min  
 Contact Resistance: 20mΩ max  
 Withstanding Voltage: 800V AC/minute  
 Temperature Range: -25C to +85C

**WAFER**

Poles: 2~15 (right angle)  
 Contact Material: Brass, Tin Plated  
 Base Material: Nylon 66 UL94V-0

Dimensions		
Poles	A	B
2	2.50	7.50
3	5.00	10.00
4	7.50	12.50
5	10.00	15.00
6	12.50	17.50
7	15.00	20.00
8	17.50	22.50
9	20.00	25.00
10	22.50	27.50
11	25.00	30.00
12	27.50	32.50
13	30.00	35.00
14	32.50	37.50
15	35.00	40.00

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/04
				Checked	Lizzy	08/10/04
				Drawn	Tina	08/10/04
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-1132R-XX**

Description: 2.50mm Crimp Style Connector Wafer

