



SPECIFICATIONS

Voltage Rating: 50V AC/DC
 Current Rating: 1A AC/DC
 Withstanding: 500V AC/minute
 Insulation Resistance: 100MΩ min
 Contact Resistance: 20mΩ max
 Material: PA66 UL94V-0
 Temperature Range: -25C to +85C
 Package: 1000 Pcs bag
 Color: Natural
 Terminal: Use JS-CH-1253

Dimensions									
Poles	A	B	C	D	Poles	A	B	C	D
2	1.00	3.00	2.40	5.00	13	12.00	14.00	13.40	16.00
3	2.00	4.00	3.40	6.00	14	13.00	15.00	14.40	17.00
4	3.00	5.00	4.40	7.00	15	14.00	16.00	15.40	18.00
5	4.00	6.00	5.40	8.00	16	15.00	17.00	16.40	19.00
6	5.00	7.00	6.40	9.00	17	16.00	18.00	17.40	20.00
7	6.00	8.00	7.40	10.00	18	17.00	19.00	18.40	21.00
8	7.00	9.00	8.40	11.00	19	18.00	20.00	19.40	22.00
9	8.00	10.00	9.40	12.00	20	19.00	21.00	20.40	23.00
10	9.00	11.00	10.40	13.00	21	20.00	22.00	21.40	23.00
11	10.00	12.00	11.40	14.00	22	21.00	23.00	22.40	24.00
12	11.00	13.00	12.40	15.00					

Series	Type	Positions
JS-CH	1253	XX
Pluggable Connectors	1.00MM Surface Mount Housing	02-22

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	09/26/05
				Checked	Lizzy	09/26/05
				Drawn	Tina	09/26/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-1253-XX**

Description: 1.00mm Crimp Style Connector