



**SPECIFICATIONS**  
Voltage Rating: 300-600 V AC/DC  
Current Rating: 9-15A AC/DC  
Contact Resistance: 20mΩ max  
Housing Material: Nylon 66 UL94V-2  
Insulation Resistance: 1,000MΩ min  
Withstanding: 1,500V AC/minute  
Operating Temp: -25°C to +85°C

Series	Type	Positions
JS-CH	2000X	XX
Pluggable Connector	Wire to Wire Housing 2000H=Plug 2000W=Receptacle	Single Row: 01, 02, 03, 04S Multi Row: 04, 06, 09, 12, 15 TH=Terminal 14-18 AWG TL=Terminal 18-22 AWG

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/15/05
				Checked	Lizzy	05/15/05
				Drawn	Tina	05/15/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

**Central Components Manufacturing**  
440 Lincoln Blvd., Middlesex, New Jersey 08846  
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-2000W-XX**

Description: .244 (6.2mm) pitch wire to wire crimp style housing & contacts