



SPECIFICATIONS

Voltage rating: 250VAC/VDC
 Current rating: 3 amps AC/DC
 Terminal material: Brass or phosphor bronze
 Terminal plating: Tin
 Contact resistance: 20 milliohms max.
 Insulation resistance: 1,000 megohms min.
 Withstanding: 1,000 VAC for 1 min.
 Temperature range: -25°C to +85°C

Quantity: 10,000 pcs/reel

Note: This terminal mates with .100" (2.54mm) and .098" (2.5mm) center crimp housings JS-8001, JS-8002) and connects to matching wafers including JS-6001, JS-7001, JS-7001-XX(L), JS-6002 and JS-7002.

Series	Material
JS-CH-8001	XXX
Center crimp terminal	T=Brass PBT=Phosphor bronze

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-8001-XXX**

Description: Center crimp terminal