



SPECIFICATIONS

Voltage rating: 250VAC/VDC
 Current rating: 3 amps AC/DC
 Contact resistance: 20 milliohms max.
 Housing material: Nylon 66, UL94V-2
 Insulation resistance: 1,000 megohms min.
 Withstanding: 1,000 VAC for 1 min.
 Temperature range: -25°C to +85°C

Packaging: 1,000 pcs/bag

Poles	A (mm)	B (mm)
02	2.50	5.80
03	5.00	8.30
04	7.50	10.80
05	10.00	13.30
06	12.50	15.80
07	15.00	18.30
08	17.50	20.80
09	20.00	23.30
10	22.50	25.80
11	25.00	28.30
12	27.50	30.80
13	30.00	33.30
14	32.50	35.80
15	35.00	38.30

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-8002-XX**

Description: Crimp style housing, 2.50mm pitch