



**SPECIFICATIONS**  
 Current Rating: 0.5A/contact  
 Voltage Rating: 30VAC/contact  
 Contact Resistance: 80 mohm Max.  
 Mating Force: 55.5N Max  
 Unmating Force: 49.0N Max.  
 Operation Temp: -20°C to +85°C

36PIN PCB FOOT PRINT

Series	Type	Style	Positions	Keying	Plating
MSAS	61	XX	36	X	XX
Mini SAS	Type 61	MV=Male Vertical SMT MS=Male Side Entry SMT FV=Female Vertical SMT FS=Female Side Entry SMT	36 Positions	Blank=None L=Left R=Right D=Dual	SGXX=Duplex GDXX=Gold XX=Flash (if blank) 15,30u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/29/07
				Checked	Lizzy	06/29/07
				Drawn	Tina	06/29/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **MSAS-61-FS-36-X-XX**

Description: Mini SAS 36Pin Receptacle Internal SMT Type