


SPECIFICATIONS
 Current Rating: 0.5A/Contact
 Voltage: 30VAC/Contact
 Contact Resistance: 80 mohm max.
 Mating Force: 55.5N Max.
 Unmating Force: 49.0N Max.
 Operating Temp: -20C to +85C



Series	Type	Style	Positions	Keying	Plating
MSAS	61	XX	36	X	XX
Mini SAS	Type 61	MV=Male Vertical SMT MS=Male Side Entry SMT FV=Female Vertical SMT FS=Female Side Entry SMT	36 Positions	Blank=None L=Left R=Right D=Dual	GDXX XX=Flash (if blank) 15,30u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
A	Spec	11/21/11	TW	Approved	Howard	06/29/07
				Checked	Lizzy	06/29/07
				Drawn	Tina	06/29/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **MSAS-61-FV-36-D-XX**

Description: Mini SAS Internal 36Pin Vertical SMT Type