



SPECIFICATIONS

Protection: IP67
 Contact Type: C: 1NOB+1NC/2NO+2NC
 Max Voltage: 250V AC/DC
 Thermal Current: 3A
 Minimum Load: 5V AC/DC 1mA
 Contact Material: Silver plated gold
 Terminal Style: .110" Solder/Quick Connect
 Contact Resistance: 50MΩ max
 Insulation Resistance: 100MΩ minimum
 Vibration Resistance: 10 to 55Hz, amplitude 1.2mm p-p
 Degree of Protection: >10g
 Electrical Life: 100,000 operations minimum
 Mechanical Life: Maintained: 1,000,000 operations min.
 Momentary: 1,000,000 operation min.
 Selector/Keylock: 250,000 operation min.
 Operating Humidity: 45 to 85% RH
 Operating Temp: -25C to +55C

Series	Type	Action	LED	Voltage
SWT	1671	X	XX	XXX
Switch	SPDT Push-Push panel mount	M=Mom—On N=On—On	RD=Red GN=Green BL=Blue YL=Yellow	6D=6.3VDC 12D=12VDC 24D=24VDC 110A=110VAC 220A=220VAC

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/08/13
				Checked	Lizzy	10/08/13
				Drawn	Tina	10/08/13
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **SWT-1671-X-XX-XXX**

Description: Stainless Steel Pushbutton Switch