





SPECIFICATIONS

Current Rating:	2 Amps
Contact Material:	Phosphor Bronze
Insulator Material:	UL94V-0 Nylon 6T, Black
Insulator Resistance:	1000 Megohms min.
Contact Resistance:	20 mohms max.
Contact Plating:	Gold Flash (std)
Withstanding:	AC 500V
Operating Temp:	-40C ~ +105C



**Recommended
P.C. Board Hole Layout**



Series	Rows	Profile	Positions	Tail	Plating	Options
BRS	02	XX	08	A	GD	HT-TB
2mm receptacle strip	02=Double	[blank]=4.3mm high	8 Positions	A=2.4 (std)	GD=Gold	TB=Tube HT=High Temp

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/13/14
				Checked	Lizzy	10/13/14
				Drawn	Tina	10/13/14
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BRS-02-08-A-GD-HT-TB**

Description: Receptacle strip, female, 8 position, double row, .079" (2.00mm) pitch, 4.4mm profile, straight type