


**SPECIFICATIONS**

Current Rating:	2.0 Amps
Insulation Resistance:	1000MΩ Min.
Withstanding:	500V AC
Contact Resistance:	20mΩ Max.
Contact Material:	Copper Alloy
Insulation Material:	Polyester, LCP, UL94V-0
Operating Temp:	-65C to +125C

Recommended  
P.C.Board  
Hole Layout



RoHS compliant

Series	Rows	Profile	Contacts	Tail Length	Options
BRS	0X	HP	XX	XX	XX
2mm Receptacle Strip	01=Single 02=Dual	HP=6.35mm	Single Row 02-40 Dual Row 04-80	TN=Tin SGXX=Selective Gold GDXX=Gold XX=Flash if blank, 10u"	[blank]=Straight SM=Surface Mount RA=Right Angle

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	01/15/09
				Checked	Lizzy	01/15/09
				Drawn	Tina	01/15/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BRS-02-HP-XX-X-XX-RA**

Description: Receptacle Strip, Double Row, .079" (2.00mm) pitch, right angle

G

G