



SPECIFICATIONS
 Current Rating: 1 Amps
 Contact Material: Phosphor Bronze
 Contact Resistance: 20 m ohms max.
 Insulator Material: Polyester, UL 94V-0
 Standard: Nylon-6T
 Insulator Resistance: 1000 Megohms min.
 Withstanding: AC 500V
 Operating Temp: -40°C ~ +105°C

Series	Rows	Profile	Positions	Tail Length	Plating
BRS	XX	HPC	XX	X	XX
2mm Receptacle Strip	01-04	HPC=6.35mm Profile	1 Row 01-40 2 Row 04-80 3 Row 09-120 4 Row 16-160	A=2.4mm C=3.0mm	TN=Tin SGXX=Selective Gold GDXX=Gold XX=Flash if Blank, 03, 05, 10, 15 u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/06/08
				Checked	Lizzy	04/06/08
				Drawn	Tina	04/06/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BRS-02-HPC-XX-X-XX**

Description: 2mm Vertical Receptacle Strip, Dual Row