



X	NOTE
5mm	02~25PINS
10mm	26~40PINS

SPECIFICATIONS
 Current Rating: 2Amp
 Contact Material: Phosphor Bronze
 Contact Resistance: 20mΩ Max.
 Insulation Material: Polyester, UL 94V-0
 Nylon 6T
 Insulation Resistance: 1000MΩ Max.
 Withstanding: 500V AC/DC
 Operating Temp: -40°C to +105°C

Series	Rows	Profile	Positions	Tail Footprint	Plating	Options
BRS	02	XX	XX	X	XX	XX
2mm Receptacle Strip	02=2 rows	LPA=2.2mm Others Available	06-80	J=5.3mm K=6.5mm	TN=Tin SG=Selective Gold GD=Gold (std)	SM=Surface Mount CP=Centering Pins PPL=Pick & Place Pads

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/26/07
				Checked	Lizzy	07/26/07
				Drawn	Tina	07/26/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BRS-02-LPA-XX-K-XX-XX**

Description: Receptacle strip, dual row 2mm x 2mm, surface mount