



SPECIFICATIONS
 Current Rating: 2Amp
 Contact Material: Phosphor Bronze
 Contact Resistance: 20mΩ Max.
 Insulation Material: Polyester, UL 94V-0
 Nylon 6T
 Insulation Resistance: 1000MΩ Min.
 Withstanding: 500V AC/DC
 Operating Temperature: -40°C to +105°C

Series	Rows	Profile	Positions	Plating	Options
BRS	XX	LPB	XX	XX	XX
2mm receptacle strip	01=Single 02=Double	LPB=4.5mm	03-40 Single row 06-80 Double row	TN=Tin GD=Gold SG=Selective Gold	SM=Surface mount CP=Centering post PPL=Pick & place pad PPT=Pick & Place Tape TR=Tape & Reel

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	09/10/99
				Checked	Lizzy	09/10/99
				Drawn	Tina	09/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles $\pm 3^\circ$
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BRS-02-LPB-XX-XX-SMCP-PPL**

Description: 2.00 Female Header Dual Rows SMT Type w/ Post and Cap