



**SPECIFICATIONS**

Current Rating:	2 Amps
Contact Material:	Phosphor Bronze
Insulator Material:	Polyester, UL94V-0 Nylon 6T
Insulator Resistance:	1000 Megohms min.
Contact Resistance:	20 mohms max.
Contact Plating:	Gold Flash (std)
Withstanding:	AC 500V
Operating Temp:	-40C ~ +105C

Series	Rows	Contacts	Tail length	Plating	Options	Package
BRS	XX	XX	X	XX	XX	XX
2mm receptacle strip	01=Single 02=Dual	Single row 1-40 Dual row 2-80	A=2.5mm CS=Custom tail	TN=Tin GD=Gold flash GD10=10 $\mu$ " gold GD15=15 $\mu$ " gold GD30=30 $\mu$ " gold	[blank]=None SM=Surface mount HT=High Temp	TY=Tray (std) TB=Tube

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/23/07
				Checked	Lizzy	04/23/07
				Drawn	Tina	04/23/07
				0.0 $\pm$ 0.35	0.00 $\pm$ 0.20	Angles $\pm$ 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BRS-02-XX-A-XX**

Description: Receptacle strip, female, double row, .079" (2.00mm) pitch, 4.4mm profile, straight type