


**SPECIFICATIONS**

Current Rating: 2.0 Amps  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding: 500V AC  
 Contact Resistance: 20mΩ Max.  
 Contact Material: Copper Alloy  
 Insulation Material: Polyester, LCP, UL94V-0  
 Operating Temp: -65C to +125C

Recommended  
 P.C.Board  
 Hole Layout



Series	Rows	Profile	Contacts	Tail Length
BRS	0X	HP	XX	XX
2mm Receptacle Strip	01=Single 02=Dual 03=Single Row Straight 04=Dual Row R/A	HP=6.35mm	Single Row 02-40 Dual Row 04-80	TN=Tin SGXX=Selective Gold GDXX=Gold XX=Flash if blank, 10u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	01/15/09
				Checked	Lizzy	01/15/09
				Drawn	Tina	01/15/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BRS-04-HP-XX-X-XX**

Description: Receptacle Strip, Double Row, .079" (2.00mm) pitch, right angle