



NOTES 2 AND 4 APPLY TO EXTERNAL SURF ACES/PROF ILE

SPECIFICATIONS

- Bezel material: Stainless steel 304-T, 0.40±.02mm thick (annealed)
- Cosmetic surface: No dents or wrinkles
- Condition of part: Free of burrs, dirt or oils
- Packaging: Packed to prevent damage during shipment
- Bezel plating: Electro polishing

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/27/07
				Checked	Lizzy	04/27/07
				Drawn	Tina	04/27/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **BZL-67650-A**

Description: 2-inch stainless steel bezel



Central Components Manufacturing

Product Inspection Form

Customer No.: 67650		Description: 2-inch stainless steel bezel			Catalog No.: BZL-67650-A		Factory No.: CD405962001		Test Date: 04/27/2007						
Testing Equipment		a: Caliper b: Projector c: Digital Caliper d: Testing Stick e: Visual f: 2D Projector													
No.	Design Dimension (mm)	Trial data recorded 04/27/2007										Testing Instrument	Results		
		1	2	3	4	5	6	7	8	9	10		OK	NG	
1	61.98±0.05	61.99	62.10									b	✓		
2	30.99±0.05	31.02	31.03									b	✓		
3	147.96±0.05	147.98	148.02									f	✓		
4	9.27±0.05	9.30	9.32									b	✓		
5	46.35±0.05	46.38	46.40									b	✓		
6	23.18±0.05	23.19	23.22									b	✓		
7	1.46±0.05	1.46	1.49									f	✓		
8	40.66±0.05	35.55	36.85	Adjusting tooling; will advise											
9	20.33±0.05	18.35	18.38												
10	1.02±0.05	1.05	1.07									f	✓		
11	11.98±0.05	12.0	12.02									a	✓		
12	3.62±0.05	3.65	3.67									b	✓		
13	7.27±0.05	7.29	7.31									b	✓		
14	2.54±0.05	2.55	2.58									b	✓		
15	77°±5°	78°	80°									b	✓		
16	0.80±0.05	0.82	0.85									f	✓		
17	0.63±0.05	0.65	0.66									b	✓		
18	1.27±0.05	1.27	1.30									b	✓		
Remarks:															
Appearance:		OK		Approved By: James Zai		Checked By: Chen Zhao		Tested By: Xiao Hai Xien							
Function:															