


SPECIFICATIONS

Current Rating: 1 Amp
 Contact Material: Phosphor Bronze
 Contact Resistance: 20mΩ Max.
 Insulation Material: Polyester, UL94V-0
 Insulation Resistance: 1000MΩ Min.
 Withstanding: 300V AC
 Operating Temp: -40°C to +105°C

Recommended P.C.B. Layout



RoHS compliant

Series	Rows	Profile	Positions	Tail Length	Plating
CARS	XX	XX	XX	X	XX
Receptacle Strip .050" X .100"	01=Single 02=Double	Blank=4.6mm (std) Others available	Single=03-50 Double=06-100	A=Standard CS=Customer Specified	TN=Tin SG=Selective Gold GD=Gold (std)

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	9/10/08
				Checked	Lizzy	9/10/08
				Drawn	Tina	9/10/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CARS-02-XX-X-XX**

Description: 1.27mm X 2.54mm Female Header Dual Rows DIP Type connector