



Note:

1. Seals B1 for Cable OD $\phi 4.5\text{mm}$ to $\phi 6.5\text{mm}$
2. Seals B2 for Cable OD $\phi 3.5\text{mm}$ to $\phi 5.3\text{mm}$
3. One set unassembled in one zipper bag

Item	Name	Material	Color
1	Connector	4 pin male, Nylon+GF	Black
2	Male pin	Brass 6 μ gold plated solder type	
3	Seals B1	EPDM	Black
4	Seals B2	EPDM	Black
5	Clamp ring	Nylon+GF	Black
6	Sealing nut	Nylon+GF	Black
7	Zipper bag	#1	
8	Liquid glue		

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/22/03
				Checked	Lizzy	05/22/03
				Drawn	Tina	05/22/03
				0.0 \pm 0.35	0.00 \pm 0.20	Angles \pm 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CBD-04BMMA-L180(A)**

Description: Lock type connector for field installation 180°, 4-pin male connector, male pin 5 amps