

RECOMMENDED MOUNTING HOLE
MAXIMUM PANEL THICKNESS: 5.5MM

Color note:


- Dual color options only available for dual port connectors

Item	Name	Material	Finish
1	Center contact	Phosphor bronze	Gold
2	Body	Zinc alloy	Nickel
3	Insulator	PE-606	
4	Mounting post	Brass	Tin
5	Solder tail	Brass wire	Tin
6	Washer	Steel	Nickel
7	Nut	Brass	Nickel

Series	Profile	Mounting Type	Body Style	Shell Material	Color (plastic body only)	Options
CBN	X	XX	X	X	XX	XX
BNC connector	H=High L=Low	VM=Vertical mount RM=Right-angle mount	A=#4-40 threaded sleeve B=Bayonet	M=Metal body P=Plastic body	BK=Black, WT=White, GN=Green, YL=Yellow, BL=Blue, RD=Red, RW=Red/White, RY=Red/ Yellow, BG=Blue/Green [blank]=None (metal body)	[blank]=50 ohm (standard) CP=Capacitor type DP=Dual port, R/A mount 75=75 ohm HW=Hardware & nut 30GD=30µ" gold plate BL=Board locks

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		



Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CBN-H-RM-B-M-XX-XX**

Description: BNC jack, 50 ohm, right angle, PCB mount, (hardware available)