



RECOMMENDED PC BOARD LAYOUT
WITHOUT MOUNTING POSTS

RECOMMENDED MOUNTING HOLE
MAXIMUM PANEL THICKNESS: 5.5MM

SPECIFICATIONS

Center contact: Bronze, 30µ" gold plated
 Body: Zinc alloy nickel plated
 Housing: PBT, UL94V-0
 Insulator: PE-606
 Hollow post: Bronze, tin plated
 Solder tail: Copper wire, tin plated
 Washer: Steel, nickel plated
 Nut: Brass, nickel plated

UL file no. E196498

Color note:

- Metal body only available in black
- Dual color options only available for dual port connectors

Series	Profile	Mounting Type	Body Style	Shell Material	Color (see note)		Options
CBN	X	XX	X	X	XX		XX
BNC connector	H=High L=Low	VM=Vertical mount RM=Right-angle mount	A=#4-40 threaded sleeve B=Bayonet	M=Metal body P=Plastic body	BK=Black WT=White GN=Green YL=Yellow BL=Blue	RD=Red RW=Red/White RY=Red/Yellow BG=Blue/Green	[blank]=50 ohm (standard) CP=Capacitor type DP=Dual port, R/A mount 75=75 ohm HW=Hardware & nut 30GD=30µ" gold plate BL=Board locks

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CBN-H-VM-B-P-BK-30GD**

Description: BNC vertical PCB panel mount jack, high profile, black housing, 30µ" gold plated contact, 75 ohms