



RECOMMENDED PCB BOARD LAYOUT WITHOUT MOUNTING POSTS

LOCK WASHER

1/2-28UNEF-2B CLAMP NUT

**RECOMMENDED MOUNTING HOLE
MAXIMUM PANEL THICKNESS: 5.5MM**

Material and Finish

- Center contact: Phosphor Bronze, Gold Plating
- Body: Zinc alloy, nickel plating
- Insulator: PBT UL94V-0
- Mounting post: Bronze, tin plating
- Solder tail: Copper wire, tin plating
- Washer: Steel, nickel plating
- Nut: Brass, nickel plating

RoHS compliant

Series	Profile	Mounting Type	Body Style	Shell Material	Color (see note)	Options
CBN	X	XX	X	X	XX	XX
BNC connector	H=High L=Low	VM2=Vertical mount RM=Right-angle mount	A=#4-40 threaded sleeve B=Bayonet	M=Metal body P=Plastic body	BK=Black, WT=White, GN=Green, YL=Yellow, BL=Blue, RD=Red, RW=Red/White, RY=Red/ Yellow, BG=Blue/Green	[blank]=50 ohm (standard) CP=Capacitor type DP=Dual port, R/A mount 75=75 ohm HW=Hardware & nut 30GD=30µ" gold plate BL=Board locks

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CBN-H-VM2-B-M-BK-75**

Description: BNC PCB vertical Panel Mount, black, 75 ohm version