



**SPECIFICATIONS**

- 1. Center contact: Phosphor bronze, 30µ" gold plate
- 2. Body: Die cast zinc, nickel plate
- 3. Housing: PBT, UL94V-0
- 4. Insulator: PE-606
- 5. Mounting post: Brass, tin plate
- 6. Solder tail: Brass wire, tin plate
- 7. Washer: Steel, nickel plate
- 8. Nut: Brass, nickel plate

**Color note:**

- Metal body only available in black
- Dual color options only available for dual port connectors

Series	Profile	Mounting Type	Body Style	Shell Material	Color (see note)		Options
CBN	X	XX	X	X	XX		XX
BNC connector	H=High L=Low	VM=Vertical mount RM=Right-angle mount	A=#4-40 threaded sleeve B=Bayonet	M=Metal body P=Plastic body	BK=Black WT=White GN=Green YL=Yellow BL=Blue	RD=Red RW=Red/White RY=Red/Yellow BG=Blue/Green	[blank]=50 ohm (standard) CP=Capacitor type DP=Dual port, R/A mount 75=75 ohm HW=Hardware & nut 30GD=30µ" gold plate BL=Board locks

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CBN-L-RM-B-P-BK-BL-30GD**

Description: BNC connector, low profile, right-angle PCB mount, board locks, black body, 30µ" gold plated center conductor, 50 ohms