



**SPECIFICATIONS**

Current Rating: 5A  
 Voltage Rating: 125V  
 Work Voltage: 200  
 Insulation Resistance: 1500  
 Contact Resistance: 10  
 Withstanding: 1500

Item	Name	Material	Finish
1	Female Pin	Phosphor Bronze	Silver Plating
2	Cone Pillar	Bakelite	
3	M1.7 Bolt	A3	Nickel Plating
4	Joint Nut	H59-1	Nickel Plating
5	Die Cast Shell	ZZnA14-1	Nickel Plating
6	Wire Clamp Screw	A3	Nickel Plating
7	Wire Clamp Cover	ZZnA14-1	Nickel Plating

RoHS compliant

Series	Type	Gender	Positions
CCC	564M	F	XX
Circular Connector	Wire Mount Straight	F=Female	02-09

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/01/07
				Checked	Lizzy	06/01/07
				Drawn	Tina	06/01/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CCC-564M-F-04**

Description: Circular Female Plug, 4 Pins

